

## SW1600POEIP

| SPECIFICATION     |   |
|-------------------|---|
| PROCESSOR         | Hi3518E V200                                  |
| Sensor            | 1/3 Aptina AR0130 CMOS, 3.7mm Pinhole Lens    |
| Resolution        | Main Stream: 1280x960                         |
|                   | Sub Stream: 704x576                           |
| CVBS Video Output | N/A   |
| IR-CUT            | IR-CUT Dual Light Filter Switch               |
| Video Process     | H.264 Video Compression, Dual-Stream, AVI,    |
|                   | Adjustable Stream 0.1 Mpbs-6Mpbs, 1-30fps     |
| Audio Process     | G.711 Code Standard (Optional)                |
| Net Connector     | RJ45, 10/100M, Support                        |
|                   | RTSP/FTP/PPOE?DHCP/DDNS/UPNP                  |
| Function          | Support WEB Remote Configuration, OSD, Motion |
|                   | Detection, Alarm, Input Activated Record.     |
|                   | Snapshot, CMS, Mobile Software (Iphone,       |
|                   | Blackberry, Androi, Symbian, and Windows)     |
| Mobile Monitor    | Support (Iphone, Windows Mobile, Blackberry,  |
|                   | Symbian, Android)                             |
| Power Supply      | POE, 12Vdc                                    |
| Power             | 10W   |
| Consumption       |   |
| Additional Parts  | POE (included)                                |